



Note:

1. Material:

  - 1.1 Housing: High temperature thermoplastic with g. f, UL94v-0
  - 1.2 Contact: copper alloy, t=0.20mm
  - 1.3 Shell: copper alloy, t=0.25mm

2. Specification:

  - 2.1 Current rating: 1 A Max.
  - 2.2 Dielectric withstand voltage: 100 V(ac) for 1 min.
  - 2.3 Contact resistance: 50 mW Max.
  - 2.4 Insulation resistance: 100 MW Min.
  - 2.5 Total mating force: 3.57 Kgf Max.
  - 2.6 Total unmating force: 1.0 Kgf Min. 0.81~2.05 Kgf Min. after 10000 insertion/extraction cycles
  - 2.7 Temperature range: -30°C~80°C

尺寸	允许公差
X.	±0.50
.X	±0.20
.XX	±0.10
.XXX	±0.03
角度	±1.00°

# 无锡联庭电子科技有限公司

图纸名称：  
MICRO 5P/F B TYPE 四脚沉板1\_2

图 纸 类 型

产品工程图

图纸名称·

MICRO 5P/F B TYPE 四脚沉板1.2

设计 zhuuji n

审核

31 | 产品料号 GLE-MICRO-0313

视图

1                    2                    3                    4                    5                    6                    7                    8